

SPEC SHEET



30 KW PEAK POWER (Electrical Power) **155 KM/H** MAX SPEED (Company Tested) **100 NM** PEAK MOTOR TORQUE 231 KM CITY RANGE (WMTC)





LASER

SHADOW

AIRSTRIKE



Turbo Red

Plasma Red



Afterburner Yellow

Cosmic Black

Lightning Blue

PARALLAX & RADAR CONSOLE THEMES

Stealth Grey



Supersonic Silver

Stellar White

Asteroid Grey

DYNAMIC, RACE-BRED STANCE

F SERIES -JET INSPIRED

DESIGN SERIES



MACH 2 RECON - SPEC SHEET

PERFORMANCE

POWER

30 KW

PEAK POWER (Electrical Power) 20 KW

NET POWER (ECE R85)

9.5 KW @ 3000 RPM continuous power (ECE R85)

TORQUE

100 NM PEAK MOTOR TORQUE

SPEED

155 KM/H MAX. SPEED (Company tested) 144 KM/H

7.7 SEC

0-100 KM/H

TOP SPEED (ECE R39.01)

ACCELERATION

2.8 SEC

REGENERATIVE BRAKING 10 LEVELS

DYNAMIC REGEN

RIDE MODES

GLIDE, COMBAT, BALLISTIC

REQUIRED

A1

RANGE

CITY RANGE (As per WMTC)

231 KM

143 KM HIGHWAY RANGE (As per WMTC)



VULTRAVIOLETTE AN MACH 2 RECON - SPEC SHEET

SMART TECH

VIOLETTE A.I.

DELTA WATCH	Optional
LOCKDOWN	Optional
ANTI-COLLISION WARNING SYSTEM	Optional
CRASH ALERT	Optional
DAILY RIDE ANALYTICS	Optional
CONTROL CENTER	Multi-function 5" TFT display with tactile input switch console (L+R)
OPERATING SYSTEM	UV Automotive Linux OS
SAFETY	Auto dimming LED Headlight with Ultra-V position lamp
SAFETY	
SAFETY	position lamp Dual LED tail light assembly with central
SAFETY	position lamp Dual LED tail light assembly with central brake light
SAFETY TRACTION CONTROL	position lamp Dual LED tail light assembly with central brake light Front and Rear LED Hazard Lights
	position lamp Dual LED tail light assembly with central brake light Front and Rear LED Hazard Lights Sidestand Sensor
TRACTION CONTROL	position lamp Dual LED tail light assembly with central brake light Front and Rear LED Hazard Lights Sidestand Sensor 4 levels





UTILITY

CHARGE LIMIT	Included
PARK ASSIST	Included
FIND MY F77	Included
DEEP SLEEP	Included
TPMS	Included

BATTERY SYSTEM

BATTERY PACK	SRB10
ENERGY CAPACITY	10.3 kWh
ENCLOSURE	All-Aluminum IP67-rated enclosure
BMS & SAFETY PROTOCOLS	Battery Management System with patented 5-level safety system - Mechanical, Thermal, Electrical, Electronic & Software protection

BATTERY & DRIVETAIN WARRANTY

UV CARE	5 years or 1,00,000 km included

VEHICLE WARRANTY

STANDARD WARRANTY (VEHICLE)



AND MECH 2 RECON - SPEC SHEET

CHARGING

CHARGING PORT IEC 62196-6

BOOST CHARGER

CHARGE RATE

Included

20% - 80% in 2.5 hrs

DRIVETRAIN

MOTOR

THROTTLE CONTROL

Ride-by-wire

Permanent Magnet AC Motor

MECHANICAL

FRAME	Steel Trellis with Aluminium Bulk Head
FRONT SUSPENSION	Upside-down Telescopic fork with a diameter of 41 mm. Preload adjustable
REAR SUSPENSION	Monoshock - preload adjustable
BRAKE SYSTEM	Hydraulic disc brakes with dual-channel BOSCH ABS
BRAKE CALIPERS	Front: Fixed 4-Radial Piston Type Rear: Single Piston Floating Caliper Type
BRAKE ROTOR	Front: 320mm disc Rear: 230mm disc
TYRES	Front: 110/70 R17 Rear: 150/60 R17



AND MOCH 2 RECON - SPEC SHEET

CONNECTIVITY

NETWORK	LTE connectivity with integrated eSIM
WLAN	Supports 802.11a/b/g/n/ac Wi-Fi standards
BLUETOOTH	Supports Bluetooth 5, Bluetooth low energy
POSITIONING	GPS/GLONASS

DIMENSIONS

WHEEL BASE	1340 mm
SEAT HEIGHT	800 mm
KERB WEIGHT	211 kg
GROUND CLEARANCE	160 mm